

User Manual

www.doughty-engineering.co.uk


T57102/12


Doughty 90° Fixed Coupler






 ϵ





- 1. Never exceed the Safe Working Load (SWL) shown on the clamp.
- 2. Only use the clamp within the designed tube parameters (48-51mm)
- 3. All clamps should be visually inspected before use. In the event of any damage the clamp should be taken out of service and returned to an 'Approved Doughty Service Agent' for inspection. (see our dealer locator on our web site for a comprehensive list of Authorised Service Agents)
- 4. When used in conjunction with other accessories, care must be taken to ensure that the minimum SWL of any component is not exceeded.
- 5. Doughty Engineering Ltd does not recommend using any clamps which do not fully encompass the tube for overhanging. All open clamps including hookclamps should be used in a vertical orientation only.



THIRD ANGLE PROJECTION

DOUGHTY

DOUGHTY ENGINEERING LTD

DATA SHEET

TITLE: DOUGHTY 90° FIXED COUPLER PART NOS:

T57102 - SILVER T57112 - BLACK

ALUMINIUM MATERIAL:

WEIGHT:


SWL:


750 KG FINISH: 157102 - POLISHED


T57112 - POWDER PAINTED BLACK


PARALLEL AND 90 DEGREE FIXED VERSIONS ARE AVAILABLE NOTES:


STRICTLY FOR REFERENCE PURPOSES ONLY











ITEM NO.	PART NUMBER	DESCRIPTION	Spares/QTY.
1	TH156	MACHINED DOUGHTY CLAMP BASE	2
2	TH157	MACHINED DOUGHTY CLAMP TOP	2
3	T78000	M12 X 70 EYEBOLT	2
4	F790	0.375" X 1.75" STAINLESS STEEL ROLL PIN	4
5	\$1910	M12x50 Low Head Socket Cap	1
6	TH1083	M12 WASHER - SPACER	1
7	\$1920	M12 Reduced Binx Nut	1
8	F780	M6 x 32 Roll Pin S/Steel S/Colour	1

T57102 - DOUGHTY 90° FIXED COUPLER

DOWGHTY	DRAWN	AW
INCOMPULITY	DATE	06/01/2011
NOT TO SCALE	Rev	1



Doughty Engineering Limited

CROW ARCH LANE, RINGWOOD, HANTS, BH24 1NZ. ENGLAND Telephone: +44 (0) 1425 478961 Fax: +44 (0) 1425 474481 www.doughty-engineering.co.uk email:sales@doughty-engineering.co.uk

EC DECLARATION OF CONFORMITY

Doughty Engineering Limited hereby certify that the equipment stated below has been designed to comply with all relevant sections of the specifications referenced below and complies with all the applicable Essential Requirements of the EC Directives and amendments and the National Laws and Regulations adopting these Directives.

Description: Doughty 90° Fixed Coupler

Model/s: Part No. T57102 / T57112

SWL: 750Kg **Factor:** 5:1

are in conformity with the provision of the following EC Directives:

MACHINERY DIRECTIVE 98/37/EC

Harmonised Standards applied:

EN 292-1-2:1991

BS EN ISO 9001:1994

National Technical Standards & Specifications applied:

BS 7905-1:2001

Signed:

Date:23-04-08

Name: Nigel Curtis Position: Technical Director

Martis.

Being the responsible person appointed by the manufacturer.

 ϵ

DEQ 083 Rev 4

Company Registration No. London 972614 Registered Office: Crow Arch Lane, Ringwood, Hants, BH24 1NZ Directors: M.B.Lister. J.C.G. Chiverton. N.D. Curtis. S.C. Wright





Doughty Engineering Ltd

Crow Arch Lane Ringwood, Hampshire, BH24 1NZ

Tel: +44 (0) 1425 478961 Fax: +44 (0) 1425 474481

email: sales@doughty-engineering.co.uk Web: www.doughty-engineering.co.uk

Note: Whilst every effort has been made to ensure that the information contained within this manual is correct, Doughty Engineering does not accept any liability for errors or omissions. Specifications and technical data are intended for guidance purposes only and may vary.